

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1. Product Identifier

Product Name: Rechargeable Lithium Ion Battery Pack

Product Numbers:

TJEP #115986

TJEP #115987

1.2. Intended Use of the Product

Use of the Substance/Mixture: Lithium-Ion battery pack

1.3. Name, Address, and Telephone of the Responsible Party

Company Techway Industrial Co., Ltd. No.32, 21st Road, Taichung Industrial Park, Taichung, Taiwan, R.O.C.

1.4. Emergency Telephone Number

Emergency Number: Giftinformationszentren der Bundesrepublik Deutschland

Berlin: 030/19240, Bonn: 0228/19240,

Erfurt: 0361/730 730, Freiburg: 0761/19240,

Göttingen: 0551/19 240, Homburg: 06841/19240,

Mainz: 06131/19240, München: 089/19240

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

*Classification (GHS-US)

Within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]: this mixture is not considered a hazard when used in a manner which is consistent with the labeled directions. See section 2.3 for information for hazards related to the ingredients encased within this product.

2.2. Label Elements

GHS-US Labeling

No labeling applicable this product is considered an article under the OSHA Hazard communication Standard [29 CFR 1910.1200]. See section 2.3 for hazards related to the ingredients encased within this product.

*2.3. Other Hazards

Other hazards not contributing to the classification (These represent the hazards associated with the materials encased within the product that are not available under normal conditions of use)

May form combustible dust concentrations in air

H301 - Toxic if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects



Within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]: this mixture is not considered a hazard when used in a manner which is consistent with the labeled directions. This mixture is considered an article in its final form.

This MSDS covers the hazards and information of the materials contained within the article, in the event the product is damaged or mishandled. Under normal conditions of use these chemicals are not anticipated to be available for exposure.

Substances within this product may be reactive with water, air, and are flammable if released. Thermal decomposition of this product may generate corrosive, and toxic vapors. In particular Hydrofluoric acid may be released in the case of open cells.

Hydrofluoric acid can cause severe chemical burns, is toxic by all routes of exposure, and is very reactive. Avoid extremely high or low temperatures, keep away from incompatible materials. Do not open, puncture, damage, or incinerate container.

2.4. Unknown Acute Toxicity (GHS-US):

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures**

| Name | Product Identifier | % | Classification (GHS-US) |
|------------------------------|--------------------------|--------|--|
| Manganese dioxide | (CAS No) 1313-13-9 | < 30 | Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Aquatic Chronic 2, H411 |
| Carbon | (CAS No) 7440-44-0 | < 30 | Comb. Dust Acute Tox. Not classified (Oral) |
| Nickel oxide | (CAS No) 1313-99-1 | < 30 | Skin Sens. 1, H317 Carc. 1A, H350 STOT RE 1, H372 Aquatic Chronic 4, H413 |
| Cobalt(II) oxide | (CAS No) 1307-96-6 | < 30 | Acute Tox. 3 (Oral), H301 Resp. Sens. 1B, H334 Skin Sens. 1, H317 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Aluminum Foil | (CAS No) 7429-90-5 | 2 - 10 | Not classified |
| 1,1-Difluoroethylene polymer | (CAS No) 24937-79-9 | < 10 | Not classified |
| Copper | (CAS No) 7440-50-8 | 2 - 10 | Not classified |
| Aluminum and inert materials | Not available | 5 - 10 | Not classified |
| Electrolyte | See composition below*** | <20 | See hazards below*** |

***Electrolyte Components

| Name | Product Identifier | Classification (GHS-US) |
|-------------------------------------|---------------------|---|
| Phosphate(1-), hexafluoro-, lithium | (CAS No) 21324-40-3 | Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT RE 1, H372 |
| Dimethyl carbonate | (CAS No) 616-38-6 | Flam. Liq. 2, H225 |
| Carbonate, methyl ethyl | (CAS No) 623-53-0 | Flam. Liq. 2, H225 |
| Ethylene carbonate | (CAS No) 96-49-1 | Eye Irrit. 2A, H319 |

**These composition tables represent the hazards associated with the individual ingredients within this product. The product itself is not hazardous under normal conditions of use.

Mercury content: Hg <0.1mg/kg

Cadmium content: Cd <1mg/kg

Lead content: Pb < 10mg/kg

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: The following first aid measures apply in case of exposure to the interior battery components, if the battery is damaged and exposure occurs. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Ingestion: Rinse mouth. Obtain emergency medical attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Not hazardous according to OSHA 29 CFR 1910.1200 and is considered an article. Under normal conditions of use there are no physical or health hazards associated with this product. The following symptoms apply in the event an exposure occurs to the materials housed inside the product. Contact may cause immediate severe irritation progressing quickly to chemical burns. May cause cancer. Exposure may produce an allergic reaction. Causes damage to organs through prolonged or repeated exposure.

Symptoms/Injuries After Inhalation: Exposure to materials housed in battery cells: may cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Skin Contact: Exposure to materials housed in battery cells: may cause an allergic skin reaction, may cause chemical burns.

Symptoms/Injuries After Eye Contact: Exposure to materials housed in battery cells: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Exposure to materials housed in battery cells: toxic if swallowed.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed to materials encased within the product get medical attention immediately.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Metal fire extinction powder, dry powder, sand, water spray.

Unsuitable Extinguishing Media: Do not use a heavy water stream, use of a heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but will burn at high temperatures.

Explosion Hazard: If heated above 125°C (257°F) cells can explode.

Reactivity: Thermal decomposition generates: corrosive vapors, flammable gas, toxic gas, hydrofluoric acid. Product itself is stable, but if damaged or opened, can release hydrofluoric acid on contact with water which can cause severe chemical burns, is toxic by all routes of exposure, and is very reactive.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other information: Do not allow run-off from fire fighting to enter drains or water courses. Upon thermal decomposition and high temperatures may explode, or release toxic, corrosive, and flammable gases.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Product itself under normal conditions of use is not considered hazardous, for materials housed within product: avoid all eyes and skin contact and do not breathe vapor and mist. Do not allow product to spread into the environment.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Stop leak without risks if possible.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. For product itself take up mechanically, for inner materials in the event of release from damage neutralize, and absorb material with inert material. Stop leak if possible to do so without risk. Do not allow to spread into the environment. Contact competent authority after a spill, and follow local/national regulations.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do not open or damage enclosure, or battery cell as this could cause a potential exposure and release of hazardous materials. Under normal conditions of use this product is considered an article and exposure to the ingredients contained within this product is unlikely. Substances within this product may be reactive with water, air, and are flammable if released. Thermal decomposition of this product may generate corrosive, and toxic vapors. In particular hydrofluoric acid may be released in the case of open cells. Hydrofluoric acid can cause severe chemical burns, is toxic by all routes of exposure, and is very reactive. Avoid extremely high or low temperatures, keep away from incompatible materials. Do not expose to heat, or ignition sources as this could cause an explosion. If heated above 125°C (257°F) may explode. Do not puncture or incinerate container. Avoid short circuiting the cell.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, vapors, spray from inner battery components.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container tightly closed. Store in original container. Store in a dry, cool place. Store away from ignition sources, heat, and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

Storage Temperature: 20 °C (68°F); room temperature.

7.3. Specific End Use(s)

Lithium-Ion battery pack.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

| Copper (7440-50-8) | | |
|----------------------|--------------------------------------|-----------------------|
| USA ACGIH | ACGIH TWA (mg/m ³) | 0.2 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 0.1 mg/m ³ |
| USA IDLH | US IDLH (mg/m ³) | 100 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 1 mg/m ³ |
| Aluminum (7429-90-5) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 1 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 5 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ |


8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure all national/local regulations are observed.

Personal Protective Equipment

: Not required under normal conditions of use, when handling damaged batteries: .
Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Not required under normal conditions of use, when handling damaged batteries: Chemically resistant materials and fabrics. Corrosionproof clothing.

Hand Protection

: Not required under normal conditions of use, when handling damaged batteries: Wear chemically resistant protective gloves.

Eye Protection

: Not required under normal conditions of use, when handling damaged batteries: Chemical goggles or safety glasses.

Skin and Body Protection

: Not required under normal conditions of use, when handling damaged batteries: .Wear suitable protective clothing.

Respiratory Protection

: Not required under normal conditions of use, when handling damaged batteries: Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information : When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|--|------------------------------|
| Physical State | : Solid |
| Appearance | : Manufactured Battery Cell. |
| Odor | : Odorless. |
| Odor Threshold | : No data available |
| pH | : No data available |
| Relative Evaporation Rate (butylacetate=1) | : No data available |
| Melting Point | : No data available |
| Freezing Point | : No data available |
| Boiling Point | : No data available |
| Flash Point | : No data available |
| Auto-ignition Temperature | : No data available |
| Decomposition Temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor Pressure | : No data available |
| Relative Vapor Density at 20 °C | : No data available |
| Relative Density | : No data available |
| Specific Gravity | : Not available |
| Solubility | : Insoluble in water. |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, Kinematic | : No data available |
| Viscosity, Dynamic | : No data available |
| Explosive Properties | : No data available |
| Oxidizing Properties | : No data available |
| Explosive Limits | : Not applicable |

9.2. **Other Information** No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Thermal decomposition generates: corrosive vapors, flammable gas, toxic gas, hydrofluoric acid. Product itself is stable, but if damaged or opened, can release hydrofluoric acid on contact with water which can cause severe chemical burns, is toxic by all routes of exposure, and is very reactive.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

10.4 Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials. Damaging, puncturing, or opening the battery cell.

10.5 Incompatible Materials: Strong acids, strong bases, strong oxidizers, water, seawater, moisture.

10.6 Hazardous Decomposition Products: Thermal decomposition generates: carbon oxides (CO, CO₂), corrosive vapors, toxic vapors. Can also release hydrofluoric acid on contact with water which can cause severe chemical burns, is toxic by all routes of exposure, and is very reactive.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

This product is considered an article under the OSHA Hazard communication Standard [29 CFR 1910.1200]. The information below reflects the hazards of the individual ingredients within the product, which if damaged may be released.

Acute Toxicity : Not classified

| | |
|--------------------------------------|---------------|
| Manganese dioxide (1313-13-9) | |
| LD50 Oral Rat | 9000 mg/kg |
| Dimethyl carbonate (616-38-6) | |
| LD50 Oral Rat | 13000 mg/kg |
| LD50 Dermal Rabbit | > 5 g/kg |
| LC50 Inhalation Rat (mg/l) | 140 mg/l/4h |
| Carbon (7440-44-0) | |
| LD50 Oral Rat | > 10000 mg/kg |

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|--------------|
| Nickel oxide (1313-99-1) | |
| LD50 Oral Rat | > 5000 mg/kg |

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

| | |
|--|---|
| Nickel oxide (1313-99-1) | |
| IARC group | 1 |
| National Toxicity Program (NTP) Status | 1 |

| | |
|-------------------------------------|----|
| Cobalt(II) oxide (1307-96-6) | |
| IARC group | 2B |

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Exposure to materials housed in battery cells: may cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Skin Contact: Exposure to materials housed in battery cells: may cause an allergic skin reaction, may cause chemical burns.

Symptoms/Injuries After Eye Contact: Exposure to materials housed in battery cells: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Exposure to materials housed in battery cells: toxic if swallowed.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General

: The product itself is not considered hazardous and is considered and article according to 29 CFR 1910.1200. The ecotoxicological information applies to the materials encased within the product. Very toxic to aquatic life with long lasting effects.

| | |
|--------------------------------|---|
| Copper (7440-50-8) | |
| LC50 Fish 1 | 0.0068 (0.0068 - 0.0156) mg/l (Exposure time: 96 h - Species: Pimephales promelas) |
| EC50 Daphnia 1 | 0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| EC50 Other Aquatic Organisms 1 | 0.0426 (0.0426 - 0.0535) mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static]) |
| LC 50 Fish 2 | 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Other Aquatic Organisms 2 | 0.031 (0.031 - 0.054) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static]) |

| | |
|---------------------------------|---|
| Nickel oxide (1313-99-1) | |
| LC50 Fish 1 | > 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static]) |
| EC50 Daphnia 1 | > 100 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| EC50 Other Aquatic Organisms 1 | > 127.3 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata) |

12.2. Persistence and Degradability

| | |
|--|---|
| Rechargeable Lithium Ion Battery Pack | |
| Persistence and Degradability | May cause long-term adverse effects in the environment. |
| Copper (7440-50-8) | |
| Persistence and Degradability | Not readily biodegradable. |

12.3. Bioaccumulative Potential

| | |
|--|-------------------------------|
| Rechargeable Lithium Ion Battery Pack | |
| Bioaccumulative Potential | Not established. |
| Manganese dioxide (1313-13-9) | |
| BCF fish 1 | (no bioaccumulation expected) |
| Log Pow | < 0 (at 20 °C) |

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations. Do not puncture or incinerate container.

Ecology – Waste Materials: The materials contained within this product are hazardous to the environment, do not release into the environment.

SECTION 14: TRANSPORT INFORMATION

14.1. U.S. DOT HAZARDOUS MATERIAL REGULATIONS (RE: GROUND TRANSPORT)

Proper Shipping Description:

UN3480 Lithium-ion batteries; UN3481 Lithium-ion batteries packed with or contained in equipment; Class 9.

Batteries are to be shipped in compliance with relevant requirements of HMR "49 CFR173.185".

14.2. CANADA TRANSPORT DANGEROUS GOODS (RE: GROUND TRANSPORT)

Proper Shipping Description:

UN3480 Lithium-ion batteries; UN3481 Lithium-ion batteries packed with or contained in equipment; Class 9.

Batteries are to be shipped in compliance with relevant requirements of TDG "Part 2" (Section 2.43), or TDG "Schedule 2" (Special Provision 34), as applicable.

14.3. INTERNATIONAL DANGEROUS GOODS REGULATIONS (RE: AIR, SEA, GROUND TRANSPORT)

Proper Shipping Description:

UN3480 Lithium-ion batteries; UN3481 Lithium-ion batteries packed with or contained in equipment; Class 9. Batteries are to be shipped in compliance with relevant requirements of the following DG Regulations:

- ICAO Technical Instructions or IATA Dangerous Goods Regulations (59th Edition): Packing Instructions 965; 966; 967 (Section I, or Section II, as applicable).
- IMDG Code: Packing Instruction P903, or Special Provision 188, as applicable.
- UN Model Regulations on the Transport of Dangerous Goods: Packing Instruction P903, or Special Provision 188, as applicable.
- UN European Agreements (ADR/RID/ADN): Packing Instruction P903, or Special Provision 188, as applicable. - Australian Dangerous Goods (ADG): Packing Instruction P903, or Special Provision 188, as applicable.

14.4. UN 38.3 BATTERY TRANSPORTATION TESTING:

Our products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 – T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Tests and Criteria that can be treated as "Non-Dangerous Goods".

Test results of the UN Recommendation on the Transport of Dangerous Goods

| Manual of Test and Criteria (38.3 Lithium battery) | | Test Results | Remark |
|--|------------------------|--------------|---------------|
| No | Test Item | | |
| T1 | Altitude Simulation | Pass | |
| T2 | Thermal test | Pass | |
| T3 | Vibration | Pass | |
| T4 | Shock | Pass | |
| T5 | External Short Circuit | Pass | |
| T6 | Impact | Pass | For cell only |
| T7 | Overcharge | Pass | |
| T8 | Forced discharge | Pass | For cell only |

SECTION 15: REGULATORY INFORMATION

15.1. GLOBAL INVENTORIES

TSCA: United States See Sec. 14. Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3.

DSL: Canada See Sec. 14. Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3.

ECL: Korea Compliant with, relevant transportation test requirements as described in the UN Manual

Rechargeable Lithium Ion Battery Pack

Material Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-------------------------------|--|
| | of Tests & Criteria, Part III, Sub-section 38.3. |
| PICCS: Philippines | Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3. |
| ENCS: Japan | Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3. |
| AICS: Australia | Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3. |
| IECS: China | Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3. |
| EINECS: European Union | Compliant with, relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub-section 38.3. |

15.2. SARA 313 Information:

SARA Title III Section 313: This product does not contain regulated levels of any toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR par 372.

15.3. California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This product does not contain regulated levels of any toxic chemical subject to the reporting requirements of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

15.4. WHMIS: Canadian Workplace

This product does not contain regulated levels of any toxic chemical subject to the reporting requirements

SECTION 16: OTHER INFORMATION

16.1. ABBREVIATIONS:

| | |
|-------------------------|---|
| TSCA | Toxic Substance Control Act |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous |
| OSHA | Occupational Safety and Health |
| IARC/NTP | International Agency for Research on Cancer/National Toxicology Program |
| SARA | Superfund Amendments and Reauthorization Act of 1986 |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| NIOSH/MSHA | National Institute for Occupational Safety Health/Mine Safety and Health Administration |
| WHMIS | Workplace Hazardous Materials Information System |

16.2. Other Information:

This document has been prepared in accordance with the MSDS requirements, batteries referenced herein are considered exempt articles and are not subject to the OSHA Hazard Communication Standard; therefore a SDS is not required, This sheet is being provided as a service to our customers.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation ,makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereto.