

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name:** TJEP TJEP lubricating oil / 100ml

· **Article number:** 46154

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the preparation:** Lubricant

1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

Aerochemica GmbH

Am Selder 35a

47906 Kempen

Tel.: 02152/8097-100

Fax : 02152/8097-200

· **Further information obtainable from:** Abteilung Produktsicherheit

1.4 Emergency telephone number:

Giftinformationszentrum Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ Nord),

Georg August Universität Göttingen, Zentrum Pharmakologie und Toxikologie,

Robert Koch Straße 40,

37075 Göttingen

Tel.: 0551/192 40

Fax: 0551/383 1881

E-Mail: giznord@giz-nord.de

Notrufnummer: +49(0)551/19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

R53-66: May cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: TJEP lubricating oil / 100ml




(Contd. of page 1)

- **Hazard pictograms** GHS02, GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**
Isoparaffine
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P211 Do not spray on an open flame or other ignition source.
P273 Avoid release to the environment.
P331 Do NOT induce vomiting.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 90622-58-5	Isoparaffine	 Xn R65 R53-66  Asp. Tox. 1, H304; Aquatic Chronic 4, H413	25-50%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide	substance with a Community workplace exposure limit  Press. Gas, H280	2,5-10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Trade name: TJEP lubricating oil / 100ml

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

124-38-9 carbon dioxide

IOELV Long-term value: 9000 mg/m³, 5000 ppm

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Trade name: TJEP lubricating oil / 100ml

(Contd. of page 3)

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Aerosol
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	-78 °C

· **Flash point:** > 55 °C (closed cup)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 265 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapour pressure at 20 °C:** ~ 4500 hPa

· Density at 20 °C:	0,87 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.

(Contd. on page 5)

Trade name: TJEP lubricating oil / 100ml

(Contd. of page 4)

- | | |
|---|---|
| · Solubility in / Miscibility with water: | <i>Not miscible or difficult to mix.</i> |
| · Partition coefficient (n-octanol/water): | <i>Not determined.</i> |
| · Viscosity: | |
| Dynamic: | <i>Not determined.</i> |
| Kinematic: | <i>Not determined.</i> |
| · Solvent content: | |
| Organic solvents: | <i>40,86 %</i> |
| VOC (EC) | <i>40,86 %</i> |
| · 9.2 Other information | <i>No further relevant information available.</i> |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** *No hazardous reactions known when used according to instructions.*
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *No dangerous reactions known.*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:** *No dangerous decomposition products known.*

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** *No irritant effect.*
- **on the eye:** *No irritating effect.*
- **Sensitization:** *No sensitizing effects known.*

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **Additional ecological information:**
- **General notes:**
*Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Other adverse effects** *No further relevant information available.*

EU

(Contd. on page 6)

Trade name: TJEP lubricating oil / 100ml

(Contd. of page 5)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

07 06 04*	other organic solvents, washing liquids and mother liquors
15 01 04	metallic packaging

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1950

· **14.2 UN proper shipping name**

· **ADR** 1950 AEROSOLS
 · **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Gases.
 · **Danger code (Kemler):** -
 · **EMS Number:** F-D,S-U

· **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L
 · **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
 · **Transport category** 2

(Contd. on page 7)

Trade name: TJEP lubricating oil / 100ml

(Contd. of page 6)

· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Liquefied gas

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4